# **Permit to Operate**

FACILITY: N-3696 EXPIRATION DATE 04/30/200

**LEGAL OWNER OR OPERATOR: MERCED CO DEPT OF PUBLIC WORKS** 

MAILING ADDRESS: SOLID WASTE DIVISION

MERCED, CA 95340

**FACILITY LOCATION:** 6040 N HIGHWAY 59

MERCED, CA 95340

FACILITY DESCRIPTION: LANDFILL

The Facility's Permit to Operate may include Facility-wide Requirements as well as requirements that apply to specific permit units.

The Permit to Operate remains valid through the permit expiration date listed above, subject to payment of annual permit fees and compliance with permit conditions and all applicable local, state, and federal regulations. This permit is valid only at the location specified above, and becomes void upon any transfer of ownership or location. Any modification of the equipment or operation, as defined in District Rule 2201, will require prior District approval. This permit shall be posted as prescribed in District Rule 2010.

DAVID L. CROW

Executive Director / APCO

Seyed Sadredin

Director of Permit Services

## San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-3696-0-0 **EXPIRATION DATE:** 04/30/2007

**EQUIPMENT DECRIPTION:** Facility-Wide Conditions

## PERMIT UNIT REQUIREMENTS

- 1. The owner or operator shall notify the District of any breakdown condition as soon as reasonably possible, but no later than one hour after its detection, unless the owner or operator demonstrates to the District's satisfaction that the longer reporting period was necessary. [District Rule 1100, 6.1; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)], [Federally Enforceable Through Title V]
- 2. The District shall be notified in writing within ten days following the correction of any breakdown condition. The breakdown notification shall include a description of the equipment malfunction or failure, the date and cause of the initial failure, the estimated emissions in excess of those allowed, and the methods utilized to restore normal operations. [District Rule 1100, 7.0; County Rules 110 (Fresno, Stanislaus, San Joaquin); 109 (Merced); 113 (Madera); and 111 (Kern, Tulare, Kings)], [Federally Enforceable Through Title V]
- 3. The owner or operator of any stationary source operation that emits more than 25 tons per year of nitrogen oxides or reactive organic compounds, shall provide the District annually with a written statement in such form and at such time as the District prescribes, showing actual emissions of nitrogen oxides and reactive organic compounds from that source. [District Rule 1160, 5.0], [Federally Enforceable Through Title V]
- 4. Any person building, altering or replacing any operation, article, machine, equipment, or other contrivance, the use of which may cause the issuance of air contaminants or the use of which may eliminate, reduce, or control the issuance of air contaminants, shall first obtain an Authority to Construct (ATC) from the District unless exempted by District Rule 2020 (7/21/94). [District Rule 2010, 3.0 and 4.0; 2020; and County Rule 201 (in all eight counties in the San Joaquin Valley)], [Federally Enforceable Through Title V]
- 5. The permittee must comply with all conditions of the permit including permit revisions originated by the District. All terms and conditions of a permit that are required pursuant to the Clean Air Act (CAA), including provisions to limit potential to emit, are enforceable by the EPA and Citizens under the CAA. Any permit noncompliance constitutes a violation of the CAA and the District Rules and Regulations, and is grounds for enforcement action, for permit termination, revocation, reopening and reissuance, or modification; or for denial of a permit renewal application. [District Rules 2070, 7.0; 2080; and 2520, 9.9.1 and 9.13.1], [Federally Enforceable Through Title V]
- 6. A Permit to Operate or an Authority to Construct shall not be transferred unless a new application is filed with and approved by the District. [District Rule 2031], [Federally Enforceable Through Title V]
- 7. Every application for a permit required under Rule 2010 (12/17/92) (Permits Required) shall be filed in a manner and form prescribed by the District. [District Rule 2040], [Federally Enforceable Through Title V]
- 8. The operator shall maintain records of required monitoring that include: 1) the date, place, and time of sampling or measurement; 2) the date(s) analyses were performed; 3) the company or entity that performed the analysis; 4) the analytical techniques or methods used; 5) the results of such analysis; and 6) the operating conditions at the time of sampling or measurement. [District Rule 2520, 9.5.1], [Federally Enforceable Through Title V]
- 9. The operator shall retain records of all required monitoring data and support information for a period of at least 5 years from the date of the monitoring sample, measurement, or report. Support information includes copies of all reports required by the permit and, for continuous monitoring instrumentation, all calibration and maintenance records and all original strip-chart recordings. [District Rule 2520, 9.5.2], [Federally Enforceable Through Title V]
- 10. The operator shall submit reports of any required monitoring at least every six months unless a different frequency is required by an applicable requirement. All instances of deviations from permit requirements must be clearly identified in such reports. [District Rule 2520, 9.6.1], [Federally Enforceable Through Title V]
- 11. Deviations from permit conditions must be promptly reported, including deviations attributable to upset conditions, as defined in the permit. For the purpose of this condition, promptly means as soon as reasonably possible, but no later than 10 days after detection. The report shall include the probable cause of such deviations, and any corrective actions or preventive measures taken. All required reports must be certified by a responsible official consistent with section 10.0 of District Rule 2520(6/15/95) [District Rules 2520, 9.6.2 and 1100, 7.0], [Federally Enforceable Through Title V]

- 12. If for any reason a permit requirement or condition is being challenged for its constitutionality or validity by a court of competent jurisdiction, the outcome of such challenge shall not affect or invalidate the remainder of the conditions or requirements in that permit . [District Rule 2520, 9.8], [Federally Enforceable Through Title V]
- 13. It shall not be a defense for a permittee in an enforcement action that it would have been necessary to halt or reduce the permitted activity in order to maintain compliance with the conditions of the permit. [District Rule 2520, 9.9.2], [Federally Enforceable Through Title V]
- 14. The permit may be modified, revoked, reopened and reissued, or terminated for cause. The filing of a request by the permittee for a permit modification, revocation and reissuance, or termination, or a notification of planned changes or anticipated noncompliance does not stay any permit condition. [District Rule 2520, 9.9.3], [Federally Enforceable Through Title V]
- 15. The permit does not convey any property rights of any sort, or any exclusive privilege. [District Rule 2520, 9.9.4], [Federally Enforceable Through Title V]
- 16. The Permittee shall furnish to the District, within a reasonable time, any information that the District may request in writing to determine whether cause exists for modifying, revoking and reissuing, or terminating the permit or to determine compliance with the permit. Upon request, the permittee shall also furnish to the District copies of records required to be kept by the permit or, for information claimed to be confidential, the permittee may furnish such records directly to EPA along with a claim of confidentiality. [District Rule 2520, 9.9.5], [Federally Enforceable Through Title V]
- 17. The permittee shall pay annual permit fees and other applicable fees as prescribed in Regulation III of the District Rules and Regulations. [District Rule 2520, 9.10], [Federally Enforceable Through Title V]
- 18. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to enter the permittee's premises where a permitted source is located or emissions related activity is conducted, or where records must be kept under condition of the permit. [District Rule 2520, 9.14.2.1], [Federally Enforceable Through Title V]
- 19. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to have access to and copy, at reasonable times, any records that must be kept under the conditions of the permit. [District Rule 2520, 9.14.2.2], [Federally Enforceable Through Title V]
- 20. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to inspect at reasonable times any facilities, equipment, practices, or operations regulated or required under the permit. [District Rule 2520, 9.14.2.3], [Federally Enforceable Through Title V]
- 21. Upon presentation of appropriate credentials, a permittee shall allow an authorized representative of the District to sample or monitor, at reasonable times, substances or parameters for the purpose of assuring compliance with the permit or applicable requirements. [District Rule 2520, 9.14.2.4], [Federally Enforceable Through Title V]
- 22. No air contaminants shall be discharged into the atmosphere from any source operation (as defined in District Rule 1020) for a period or periods aggregating more than 3 minutes in any one hour which is as dark or darker than Ringelmann #1 or equivalent to 20% opacity and greater, unless specifically exempted by District Rule 4101 (12/17/92), by using EPA method 9. If the equipment or operation is subject to a more stringent visible emission standard as prescribed in a permit condition, the more stringent visible emission limit shall supersede this condition. [District Rule 4101, and Merced County Rule 401], [Federally Enforceable Through Title V]
- 23. No person shall supply, sell, solicit or apply any architectural coating, except specialty coatings, that contains more than 250 grams of VOC per liter of coating (less water and exempt compounds, and excluding any colorant added to tint bases), or manufacture, blend, or repackage such coating with more than 250 grams of VOC per liter (less water and exempt compounds, and excluding any colorant added to tint bases) for use within the District. [District Rule 4601, 5.1], [Federally Enforceable Through Title V]
- 24. No person shall apply, sell, solicit, or offer for sale any specialty architectural coating listed in the Table of Standards (District Rule 4601, Table 1 (12/17/92)), nor manufacture, blend, or repackage such coating for use within the District, which contains VOCs (less water and exempt compounds, excluding any colorant added to tint bases) in excess of the specified limits listed in Table 1 of Rule 4601 (12/17/92). [District Rule 4601, 5.2], [Federally Enforceable Through Title V]
- 25. All VOC-containing materials shall be stored in closed containers when not in use. In use includes, but is not limited to: being accessed, filled, emptied, maintained or repaired. [District Rule 4601, 5.4], [Federally Enforceable Through Title V]
- 26. A person shall not use VOCs for the cleanup of spray equipment unless equipment for collection of the cleaning compounds and minimizing its evaporation to the atmosphere is used. [District Rule 4601, 5.5], [Federally Enforceable Through Title V]
- 27. The permittee shall comply with all the Labeling and Test Methods requirements outlined in Rule 4601 sections 6.1 and 6.2 (12/17/92). [District Rule 4601, 6.1 and 6.2], [Federally Enforceable Through Title V]
- 28. With each report or document submitted under a permit requirement or a request for information by the District or EPA, the permittee shall include a certification of truth, accuracy, and completeness by a responsible official. [District Rule 2520, 9.14.1 and 10.0], [Federally Enforceable Through Title V]
- 29. If the permittee performs maintenance on, or services, repairs, or disposes of appliances, the permittee shall comply with the standards for Recycling and Emissions Reduction pursuant to 40 CFR Part 82, Subpart F. [40 CFR 82 Subpart F], [Federally Enforceable Through Title V]

- 30. If the permittee performs service on motor vehicles when this service involves the ozone-depleting refrigerant in the motor vehicle air conditioner (MVAC), the permittee shall comply with the standards for Servicing of Motor Vehicle Air Conditioners pursuant to all the applicable requirements as specified in 40 CFR Part 82, Subpart F, [40 CFR Part 82, Subpart F], [Federally Enforceable Through Title V]
- 31. Disturbances of soil related to any construction, demolition, excavation, extraction, and other earthmoving activities shall comply with the requirements for fugitive dust control in Rule 8021 (11/15/01) unless specifically exempted under section 4.0 of Rule 8021. [District Rule 8021], [Federally Enforceable Through Title V]
- 32. Outdoor handling, storage, and transport of any bulk material shall comply with the requirements of Rule 8031 (11/15/01), unless specifically exempted under section 4.0 of Rule 8031. [District Rule 8031], [Federally Enforceable Through Title V]
- 33. All operational landfills shall comply with the requirements of District Rule 8041 (11/15/01). This condition also applies to closure activities and closed landfill sites when activities are conducted which disturb surface soils covering an area greater than one (1) acre. [District Rule 8041], [Federally Enforceable Through Title V]
- 34. Any open area having 3.0 acres or more of disturbed surface area, that has remained undeveloped, unoccupied, unused or vacant for more than seven days shall comply with the requirements of Rule 8051 (11/15/01), unless specifically exempted under section 4.0 of Rule 8051. [District Rule 8051], [Federally Enforceable Through Title V]
- 35. Any new or existing public or private paved or unpaved road, road construction project, or road modification project shall implement the control measures and design criteria of, and comply with the requirements of Rule 8061 (11/15/01) unless specifically exempted under section 4.0 of Rule 8061. [District Rule 8061], [Federally Enforceable Through Title V]
- 36. Any unpaved vehicle/equipment traffic area of 1.0 acre or larger shall comply with the requirements of Rule 8071 (11/15/01), unless specifically exempted under section 4.0 of Rule 8071. [District Rule 8071], [Federally Enforceable Through Title V]
- 37. Any owner or operator of a demolition or renovation activity, as defined in 40 CFR 61.141, shall comply with the applicable inspection, notification, removal, and disposal procedures for asbestos containing materials as specified in 40 CFR 61.145 (Standard for Demolition and Renovation). [40 CFR 61 Subpart M], [Federally Enforceable Through Title V]
- 38. The permittee shall submit certifications of compliance with the terms and standards contained in Title V permits, including emission limits, standards and work practices, to the District and the EPA annually (or more frequently as specified in an applicable requirement or as specified by the District). The certification shall include the identification of each permit term or condition, the compliance status, whether compliance was continuous or intermittent, the methods used for determining the compliance status, and any other facts required by the District to determine the compliance status of the source. [District Rule 2520, 9.17], [Federally Enforceable Through Title V]
- 39. Any Title V permittee shall submit an application permit renewal to the District at least six months, but not greater than 18 months, prior to the Title V permit expiration date. [District Rule 2520, 5.2], [Federally Enforceable Through Title V]
- 40. When a term is not defined in a Title V permit condition, the definition in the rule cited as the origin and authority for the condition in a Title V permit shall apply. [District Rule 2520, 9.1.1], [Federally Enforceable Through Title V]
- 41. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following outdated SIP requirements: Rule 401 (Madera, Fresno, Kern, Kings, San Joaquin, Stanislaus, Tulare and Merced), Rule 110 (Fresno, Stanislaus, San Joaquin), Rule 109 (Merced), Rule 113 (Madera), Rule 111 (Kern, Tulare, Kings), Rules 201, 202, 203, 208, and 209 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced, San Joaquin), Rule 204 (Fresno, Kern, Tulare, Kings, Madera, Stanislaus, Merced), Rule 206 (San Joaquin), Rule 410.1 (Kern), and Rule 423 (Kern, Fresno, Stanislaus, San Joaquin). A permit shield is granted from these requirements. [District Rule 2520, 13.2], [Federally Enforceable Through Title V]
- 42. Compliance with permit conditions in the Title V permit shall be deemed compliance with the following applicable requirements: SJVUAPCD Rules 1100, sections 6.1 and 7.0 (12/17/92); 2010, sections 3.0 and 4.0 (12/17/92); 2031 (12/17/92); 2040 (12/17/92); 2070, section 7.0 (12/17/92); 2080 (12/17/92); 4101 (12/17/92); 4601, sections 5.1, 5.2, 5.4, 5.5, 6.1, and 6.2 (12/17/92); 8020 (4/25/96); 8030 (4/25/96); 8040 (4/25/96); 8060 (4/25/96); and 8070 (4/25/96). A permit shield is granted from these requirements. [District Rule 2520, 13.2], [Federally Enforceable Through Title V]
- 43. No air contaminant shall be released into the atmosphere which causes a public nuisance. [District Rule 4102], [Federally Enforceable Through Title V]
- 44. On December 31, 2002, the initial Title V permit was issued. The reporting periods for the Report of Required Monitoring and the Compliance Certification Report are based upon this initial permit issuance date, unless alternative dates are approved by the District Compliance Division. These reports are due within 30 days after the end of the reporting period. [District Rule 2520], [Federally Enforceable Through Title V]

## San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-3696-1-1 **EXPIRATION DATE:** 04/30/2007

#### **EQUIPMENT DECRIPTION:**

ONE 1,000 GALLON STEEL TANK INSTITUTE FIREGUARD ABOVEGROUND GASOLINE STORAGE TANK SERVED BY A TWO POINT PHASE I VAPOR RECOVERY SYSTEM (G-70-162) AND 1 GASOLINE DISPENSING NOZZLE SERVED BY BALANCE PHASE II VAPOR RECOVERY SYSTEM (G-70-162)

## PERMIT UNIT REQUIREMENTS

- 1. This gasoline storage and dispensing equipment shall not be used in retail sales, where gasoline dispensed by the unit is subject to payment of California sales tax on gasoline sales. [District Rule 2520, 9.1], [Federally Enforceable Through Title V]
- 2. Each gasoline storage tank shall be equipped with a permanent submerged fill pipe. [District Rule 4621, 5.1.1], [Federally Enforceable Through Title V]
- 3. Each storage tank subject to this permit shall be equipped with an ARB certified Phase I vapor recovery system, which shall prevent at least 95% by weight of all gasoline vapors displaced during the filling of storage tanks from entering the atmosphere. The transfer of gasoline from any delivery vessel to any stationary storage container with 250 gallon capacity or more shall not be allowed unless the container is equipped with an ARB certified Phase 1 system and maintained and operated according to manufacturers specifications. [District Rule 4621, 3.1 and 5.1.1], [Federally Enforceable Through Title V]
- 4. No gasoline delivery vessel shall be operated or be allowed to operate unless valid State of California decals are displayed on the cargo tank which attest to the vapor integrity of the tank. [District Rule 4621, 5.2.1], [Federally Enforceable Through Title V]
- 5. Each dispensing system shall be equipped with an ARB certified Phase II vapor recovery system which shall prevent at least 95% by weight of all gasoline vapors displaced during refueling of vehicles from entering the atmosphere. [District Rule 4622, 5.1], [Federally Enforceable Through Title V]
- 6. Compliance with the requirement of the Phase II system to be 95% effective for displaced vapors is considered to be demonstrated by passing performance tests, at least once every year from the date of the most recent test, or at more frequent intervals, as specified by the ARB Executive Order certifying the system. Facilities shall be tested in accordance with BAAQMD Source Test Procedures ST-27 (Dynamic Back Pressure) and ST-38 (Static Leak Test Procedure Aboveground Tanks). [District Rules 2520, 9.4.2 and 4622, 5.2, 6.2. 6.3], [Federally Enforceable Through Title V]
- 7. Each ARB certified vapor recovery system shall be tested within 60 days of major modification or installation, except as otherwise allowed by this permit. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. [District Rule 4622, 6.2.2], [Federally Enforceable Through Title V]
- 8. The ARB certified vapor recovery system and all of its components shall be maintained in good repair. Any ARB certified gasoline vapor recovery system, which has been installed and has been issued a permit to operate, shall not be removed regardless of the amount of gasoline dispensed or how the gasoline is delivered to the facility. [District Rule 4622, 5.3], [Federally Enforceable Through Title V]
- 9. No gasoline shall be transferred into vehicle fuel tanks if the vapor recovery system contains any defect listed in Section 94006 of Title 17 of the California Code of Regulations or in Section 5.4 of SJVUAPCD Rule 4622 (as amended February 17, 1994) until the defect has been repaired, replaced, or adjusted as necessary to correct the defect, and the District has reinspected the system or has authorized its use pending reinspection. [District Rule 4622, 5.4], [Federally Enforceable Through Title V]
- 10. Any defects identified shall be tagged "Out of Order"; the tagged equipment shall be rendered inoperable and the tag(s) shall not be removed until the defect has been repaired, replaced or adjusted. In the case of defects identified by the District, tagged equipment shall be rendered inoperable and the tag shall not be removed until the District has been notified of the repairs, and/or the District has inspected and authorized the tagged equipment for use. A log containing at least the following shall be maintained: date and type of defect identified and date repaired, replaced or corrected. [District Rules 2520, 9.4.2 and 4622, 5.5], [Federally Enforceable Through Title V]
- 11. Vapor recovery systems and gasoline dispensing equipment shall be maintained leak-free as verified using EPA Test Method 21 and visual inspection. Leak testing shall be performed at least annually and within 60 days of all major modifications. For this condition, a major modification is considered to be replacing, repairing, or upgrading 75% or more of the certified system. A leak is defined as the dripping at a rate of more than three (3) drops per minute of liquid containing VOCs or a reading as methane in excess of 10,000 ppm as determined using EPA Method 21. [District Rules 2520, 9.4.2 and 4622, 3.6, 5.6], [Federally Enforceable Through Title V]

- 12. Each operator shall maintain a leak inspection log containing, at a minimum, the following: inspector's name, location and description of component type where any leak is found; date of leak detection, emission level (ppm) if applicable, and date leak is repaired. [District Rule 2520, 9.4.2], [Federally Enforceable Through Title V]
- 13. No person shall top off a motor vehicle fuel tank. [District Rule 4622, 5.9], [Federally Enforceable Through Title V]
- 14. No owner or operator shall tamper with, or permit tampering with, the ARB certified vapor recovery system in a manner that would impair the operation or effectiveness of the system. [District Rule 4622, 5.11], [Federally Enforceable Through Title V]
- 15. Pressure/Vacuum relief valves shall be maintained operational at all times. [District Rule 4622]
- 16. The District shall be notified by the permittee 15 days prior to each test. The test results shall be submitted to the District no later than 30 days after each test. [District Rule 1081]
- 17. Operator shall maintain all records of required monitoring data and support information for inspection for a period of five years. [District Rule 2520, 9.4.2], [Federally Enforceable Through Title V]

## San Joaquin Valley Air Pollution Control District

**PERMIT UNIT:** N-3696-2-2 **EXPIRATION DATE:** 04/30/2007

#### **EQUIPMENT DECRIPTION:**

MUNICIPAL SOLID WASTE LANDFILL (115 ACRES), INCLUDING LANDFILL GAS COLLECTION SYSTEM WITH GAS EXTRACTION BLOWER, COLLECTION PIPING NETWORK, GAS/LIQUID SEPARATOR, CONTROLED BY A CARBON ADSORPTION UNIT

## PERMIT UNIT REQUIREMENTS

- 1. Tier 2 specifications to determine the site-specific NMOC concentration shall include the following: 1) For sampling, at least 2 sample probes shall be installed per hectare of landfill surface that has retained waste for at least 2 years, up to a maximum of 50 required probes. One sample of landfill gas shall be collected from each probe to determine the NMOC concentration, using EPA Method 25, 25C, another method approved by the EPA, or 18, in accordance with 40 CFR 60.754(a)(3). If EPA Method 18 is used, the minimum list of compounds to be tested shall be those published in the most recent Compilation of AP-42. If composite sampling is used, equal sample volumes are required. All samples taken shall be used in the analysis. The NMOC concentration from Method 25 or 25C shall be divided by 6 to convert from C-NMOC, as carbon to as hexane. 2) For landfills equipped with active collection systems, samples may be collected from the common header pipe before gas moving or condensate removal equipment; a minimum of 3 samples must be collected. [40 CFR 60.754(a)(3) and (a)(5)], [Federally Enforceable Through Title V]
- 2. Tier 2 specifications to determine the site-specific NMOC concentration shall include the following: 1)The NMOC mass emission rate shall be recalculated using the average site-specific concentration, instead of the default value, 2) If the resulting calculated mass emission rate is equal to or greater than 50 megagrams/year, the landfill owner or operator shall either comply with 60.752(b)(2), or determine a site-specific methane generation rate constant and recalculate the NMOC emission rate using Tier 3 specifications. [40 CFR 60.754(a)(3)(i)&(ii)], [Federally Enforceable Through Title V]
- 3. If the calculated NMOC mass emission rate, using the site-specific NMOC concentration, is less than 50 megagrams/year, then a periodic estimate of the emission rate report, pursuant to 60.757(b)(1) shall be submitted to the Administrator. The site-specific NMOC concentration shall be retested every 5 years, using Tier 2 specifications. [40 CFR 60.754(a)(3)(iii)], [Federally Enforceable Through Title V]
- 4. Tier 3 specifications to determine the site-specific methane generation rate constant shall include the following: 1) EPA Method 2E or another method approved by the EPA shall be used, 2) The NMOC mass emission rate shall be recalculated using the average site-specific NMOC concentration and the site-specific methane generation rate constant k, instead of the default values in 40 CFR 60(a)(1), and 3) If the resulting calculated NMOC mass emission rate is equal to or greater than 50 megagrams/year, the landfill owner or operator shall comply with 60.752(b)(2). [40 CFR 60.754(a)(4), (a)(5) and (i)], [Federally Enforceable Through Title V]
- 5. If Tier 3 specifications are used to determine the site-specific methane generation rate and the calculated NMOC mass emission rate is less than 50 megagrams/year, then a periodic emission rate report shall be submitted to the Administrator, pursuant to 60.757(b)(1) and the NMOC concentration shall be recalculated annually, pursuant to 60.757(b)(1), using the site-specific methane generation rate constant and the NMOC concentration obtained using Tier 2 specifications. Determination of the site-specific methane generation rate constant is performed once and used in all subsequent annual NMOC emission rate calculations. [40 CFR 60.754(a)(4)(ii)], [Federally Enforceable Through Title V]
- 6. For PSD purposes, the NMOC emission rate shall be estimated and compared to the PSD major source and significance levels in 40 CFR 51.166 or 52.21, using AP-42 or EPA-approved procedures. [40 CFR 60.754(c)], [Federally Enforceable Through Title V]
- 7. The NMOC emission rate shall be recalculated and reported to the APCO annually, except as otherwise provided in this permit, until such time as the calculated NMOC emission rate is equal to or greater than 50 megagrams/year and a collection and control system is installed or until the landfill is closed. [40 CFR 60.752(b)(1), 60.754(a) and 60.757(b)], [Federally Enforceable Through Title V]
- 8. If the NMOC emission rate, as reported in the annual report is less than 50 megagrams/year in each of the next 5 consecutive years, the owner or operator may elect to submit an estimate of the NMOC emission rate for the next 5-year period in lieu of the annual reports for those 5 years. This estimate shall include the current amount of solid waste-in-place and the estimated waste acceptance rate for each year of the 5 years. All data and calculations upon which this estimate is based shall be provided to the APCO. This estimate shall be revised at least once every 5 years. [40 CFR 60.757(b)(1)(ii)], [Federally Enforceable Through Title V]
- 9. If the actual waste acceptance rate exceeds the estimated rate used in any year reported in a 5-year estimate of the NMOC emission rate, then a revised 5-year estimate shall be submitted to the APCO. The revised estimate shall cover the 5-year period beginning with the year in which the actual waste acceptance rate exceeded the estimated acceptance rate. [40 CFR 60.757(b)(1)(ii)], [Federally Enforceable Through Title V]

- 10. The NMOC emission rate report shall include all the data, calculations, sample reports and measurements used to estimate the annual or 5-year emissions. [40 CFR 60.757(b)(2)], [Federally Enforceable Through Title V]
- 11. If the owner or operator elects to recalculate the NMOC emission rate using Tier 2 specifications and the resulting NMOC emission rate is less than 50 megagrams/year, annual periodic reporting shall resume. The revised NMOC emission rate report, with the recalculated NMOC emission rate using Tier 2 specifications, shall be submitted within 180 days of the first Tier 1 calculated exceedance of 50 Megagrams/year. [40 CFR 60.757(c)(1)], [Federally Enforceable Through Title V]
- 12. If the owner or operator elects to recalculate the NMOC emission rate using Tier 3 specifications and the resulting NMOC emission rate is less than 50 megagrams/year, annual periodic reporting shall resume. The revised NMOC emission rate report, with the recalculated NMOC emission rate using Tier 3 specifications, shall be submitted within 1 year of the first Tier 1 calculated exceedance of 50 Megagrams/year. [40 CFR 60.757(c)(2)], [Federally Enforceable Through Title V]
- 13. Each owner or operator shall keep for at least 5 years up-to-date, readily accessible, on-site records of the maximum design capacity, the current amount of solid waste in-place, and the year-by-year waste acceptance rate. Off-site records may be maintained if they are retrievable within 4 hours. [40 CFR 60.758(a) and District Rule 2520, 9.4.2], [Federally Enforceable Through Title V]
- 14. This operating permit may be cancelled with APCO approval when the landfill is closed, pursuant to the requirements of this permit, if the landfill is not otherwise subject to the requirements of either 40 CFR part 70 or part 71 and if either 1) it was never subject to the requirement for a control system under 40 CFR 60.752(b)(2); or 2) the owner or operator meets the conditions for control system removal specified in 40 CFR 60.752(b)(2)(v). [40 CFR 60.752(d)], [Federally Enforceable Through Title V]
- 15. If the landfill is permanently closed, a closure notification shall be submitted to the APCO within 30 days of waste disposal cessation. A permanent closure must take place in accordance with 40 CFR 258.60. If a closure report has been submitted, no additional waste may be placed in the landfill without filing a notification of modification to the APCO, pursuant to 40 CFR 60.7(a)(4). [40 CFR 60.752(b)(1)(ii)(B), 60.757(d)], [Federally Enforceable Through Title V]
- 16. If the calculated NMOC is equal to or greater than 50 megagrams/year, the owner or operator shall install a collection and control system, that effectively captures the gas generated within the landfill, within 30 months of that determination. This operating permit must be modified accordingly to show compliance with 40 CFR 62, Subpart GGG requirements applicable to a MSWL with a collection and control system. [40 CFR 60.752(b)(2)(ii), 60.753, 60.755 and 60.756], [Federally Enforceable Through Title V]
- 17. If a gas collection and control system is installed, it shall comply with the operational standards of 40 CFR 60.753, the compliance provisions of 40 CFR 60.755, the monitoring provisions of 40 CFR 60.756, the reporting and record keeping requirements of 40 CFR 60.757 and 60.758, and the requirements of 40 CFR 60.759 (for active collection systems). [40 CFR 60.752(b)(2)(ii), 60.753, 60.755, 60.756, 60.757, 60.758 and 60.759], [Federally Enforceable Through Title V]
- 18. Upon receiving an approved plan for closure, or partial closure, the operator shall modify this operating permit to comply with the requirements of District Rule 4642. [District Rule 4642, 3.2 and 4.1.1], [Federally Enforceable Through Title V]
- 19. All equipment shall be maintained in good operating condition and shall be operated in a manner to minimize emissions of air contaminants into the atmosphere. [District Rule 2201], [Federally Enforceable Through Title V]
- 20. All equipment shall be constructed, maintained and operated according to the specifications and plans contained in the permit application except as otherwise specified herein. [District Rule 2201], [Federally Enforceable Through Title V]
- 21. The entire gas collection system shall be inspected for leaks with a portable analyzer in accordance with EPA Method 21 at least quarterly. After four successful inspections, the frequency shall be annually. If a leak is detected, quarterly inspections shall resume. A leak is defined as a measurement in excess of 1,000 ppm (measured as methane) above background when measured at a distance of one (1) centimeter from the potential source. Leaks shall be repaired within 15 calendar days after it is detected. [District Rule 2520, 9.3.2], [Federally Enforceable Through Title V]
- 22. Sampling ports adequate for extraction of grab samples, measurement of gas flow rate, and use of an FID, PID, or other District-approved VOC detection device shall be provided for both the influent and the effluent gas streams. [District Rule 1081], [Federally Enforceable Through Title V]
- 23. Ongoing compliance with VOC emission rate and control efficiency requirements shall be demonstrated by sampling both the influent and the effluent gas streams with an FID, PID, or other District-approved VOC detection device. [District Rule 1081], [Federally Enforceable Through Title V]
- 24. Sampling to demonstrate ongoing compliance shall be performed at least once per week. [District Rule 1081], [Federally Enforceable Through Title VI
- 25. A minimum of two (2) 250-pound carbon canisters which are connected in series shall be utilized. [District Rule 2201], [Federally Enforceable Through Title V]
- 26. The carbon canisters removed from the system shall be sealed vapor tight. [District Rule 2201], [Federally Enforceable Through Title V]
- 27. Neither the soil ventilation rate nor the effluent gas flow rate shall exceed 38 scfm. [District Rule 2201], [Federally Enforceable Through Title V]

- 28. Either the VOC control efficiency shall not be less than 98%, or the total VOC emission rate shall not exceed 2 pounds in any one day. [District Rule 2201], [Federally Enforceable Through Title V]
- 29. The VOC concentration of the effluent gas from the vapor collection system served by carbon canisters shall not exceed 28 ppmv as hexane. [District Rule 2201], [Federally Enforceable Through Title V]
- 30. Records of the cumulative running time and the measured influent and effluent VOC concentrations shall be maintained. Records of system inspections including: date, time and inspection results shall be maintained. All records shall be retained on the premises for at least five years and made available for District inspection upon request. [District Rule 2201], [Federally Enforceable Through Title V]